

Typical Applications

Analytical

Biotech

Industrial

Laser



Metrology

Pharmaceutical

Packaging

Printing

Research



Thermo Scientific
ThermoFlex Series Recirculating Chillers

configurable,
innovative, performance

The Ideal Choice

Temperature control
products for
your application

As an innovative leader in temperature control, **we have the expertise to enable our customers to optimize liquid cooling and heating applications.** With over 50 years of service and countless successful installations around the world, we collaborate with you to provide product and applications expertise to meet the most demanding temperature control requirements. From biotech and pharmaceutical to printing and semiconductor, companies around the world, continue to make Thermo Scientific temperature control products the ideal choice.

Select the product that is right for your application from a comprehensive portfolio of temperature control solutions that deliver scalable product offerings ranging from bench top research to large process manufacturing. Our new and innovative products – developed from customer feedback – represent a leap forward in performance, configurability and technology that provide the following advantages:

The Ideal Choice: Whatever your application or your budget, you can configure a flexible, cost-effective temperature control system that suits your specific requirements.

Innovation: Our research and development team is focused on designing innovative products based on your feedback.

Global Service and Support: With our extensive global footprint, service and support are readily available by phone or the web.



Thermo Scientific ThermoFlex Series recirculating chillers

Configurable Design: Choose from a wide range of cooling capacities and options to create the perfect fit for your application.

Innovative Platform: Developed with your input from concept to design. The result is an easy-to-use, easy-to-maintain high performance chiller configurable to the most demanding applications.

Excellent Performance: Optimized cooling capacity and reliability for your critical application needs.

Choose your controller

Feature	Standard	Deluxe ¹
LCD Multi-line display		●
LED Single-line display	●	
Alphanumeric display		●
Temperature alarms	●	●
Pressure alarms	●	●
Flow alarms	●	●
Fluid level readout		●

¹ Deluxe controller is available on the ThermoFlex 900 - 10000 models only.

See last page for list of accessories!

Choose your features

Feature	Benefit	Availability
Pressure Relief⁴	The internal pressure relief valve allows you to limit the maximum fluid pressure to meet the application requirements .	900 to 10000
Pressure Relief with Flow Readout⁴	The pressure relief valve allows you to limit the maximum fluid pressure to meet the application requirements. The flow readout allows you to monitor the flow rate to the application and set flow alarms via the controller.	900 to 10000
Flow Control with Flow Readout	The flow control valve allows you to adjust the flow to the application. Monitor flow rate to application and set flow alarms via controller.	All models
Global Voltage	Select the appropriate frequency and voltage to enable operation anywhere in the world.	900 to 10000
SEMI S2 Compliance	Compliant with S2-0703, S8-0705, S14-0704, F47-0706. Includes EMO capability/LOTO circuit breaker (GFCI available on standard temperature range).	900 to 10000
Water-Cooled Condenser	Reduces heat rejection into your workspace by using facility water.	1400-24000
Air-Cooled Condenser	Simplified installation (no facility water required).	All models
Anti Drainback	Prevents fluid from flowing back to the reservoir when the chiller is installed below the application.	All models
Auto Refill	Automatic refilling from a facility-supplied water source to ensure the proper fluid level is maintained.	All models
DI Water²	Partial flow internal DI (De-ionized water support) cartridge minimizes footprint and provides fluid resistivity between 1- 3 MΩ - cm.	All models
DIC Water³	Partial flow internal DI cartridge minimizes footprint and provides fluid resistivity between 1-3 M-cm with DI level control/monitoring on deluxe controller.	900 -10000
RS232 & RS485 Digital/Analog Communication	Provides analog and digital communication for remote operation, monitoring and data logging. Includes a remote sensor port which allows for remote temperature control of an application when used with remote sensor (available as an accessory).	All models

² Basic controller only



³ Deluxe controller and Standard Temperature range only

⁴ P1, P2, and T1 pumps only



900 to 2500 watts of cooling



Specifications	ThermoFlex 900	ThermoFlex 1400	ThermoFlex 2500
Standard Setpoint Temperature Range	5 °C to 40 °C (41 °F to 104 °F)		
Optional Setpoint Temperature Range	—	5 °C to 90 °C (41 °F to 194 °F)	
Ambient Temperature Range	10 °C to 40 °C (50 °F to 104 °F)		
Temperature Stability	±0.1 °C		
Standard Cooling Capacity 60 Hz at 20°C 50 Hz at 20°C	900 W / 3074 BTU 750 W / 2651 BTU	1400 W / 4781 BTU 1170 W / 3996 BTU	2500 W / 8538 BTU 2200 W / 7513 BTU
Reservoir Volume	7.2 Liters (1.9 gallons)		
Refrigerant	R134A		
Physical Dimensions (H x W x D) Air-Cooled	27.3 x 14.2 x 24.6 in (69.2 x 36.0 x 62.4 cm)	27.3 x 14.2 x 24.6 in (69.2 x 36.0 x 62.4 cm)	29.0 x 17.2 x 26.5 in (73.6 x 43.6 x 67.3 cm)
Water-Cooled	—	27.3 x 14.2 x 24.6 in (69.2 x 36.0 x 62.4 cm)	29.0 x 17.2 x 26.5 in (73.6 x 43.6 x 67.3 cm)
P1 — Positive Displacement Pump 60 Hz	2.1 gpm @ 60 psig (7.9 lpm @ 4.1 bar)		
50 Hz	1.7 gpm @ 60 psig (6.4 lpm @ 4.1 bar)		
P2 — Positive Displacement Pump 60 Hz	4.0 gpm @ 60 psig (15.1 lpm @ 4.1 bar)		
50 Hz	3.3 gpm @ 60 psig (12.5 lpm @ 4.1 bar)		
T1 — Turbine Pump* 60 Hz	3.5 gpm @ 60 psid (13.2 lpm @ 4.1 bar)		
50 Hz	2.5 gpm @ 60 psid (9.5 lpm @ 4.1 bar)		
Chiller Weight (with P2 pump)	130.5 lb (59.2 kg)		175.5 lb (79.6 kg)
Voltage Options 115 V/60 Hz & 100 V/50 Hz ^{1,2} 100 V/60 Hz & 100 V/50 Hz ^{1,2} 208-230 V/60 Hz & 200 V/50 Hz ^{1,2} 230 V/50 Hz ¹ 200-230 V/50-60 Hz Global Voltage ^{1,2}	Available Available Available Available Available		— — Available Available Available
Compliance	 		¹ CE compliant ² CSA compliant


Specifications obtained at sea level using water as the recirculating fluid, at a +20°C process setpoint, +25°C ambient condition, at nominal operating voltage. Other fluids, process temperatures, ambient temperatures, altitude or operating voltages will affect performance. Specifications subject to change.

*Pressure values for turbine pumps are differential pressures between the inlet and the outlet of the chiller.


pumping capacity

cooling capacity

P1 & P2 Pump





ThermoFlex 900, 1400 & 2500



Cooling capacity based on chillers with P2 pumps set at 10 gpm. Other pumps and flow rates will affect cooling capacity performance.


T1 Pump



Full flow filter ensures clean fluid to protect your application and maximize recirculation system life.

Easily removable condenser grill and air filter allow for quick and simple cleaning to optimize chiller performance and maximize component life.


Integrated funnel for easy filling.



3500 to 10000 watts of cooling



3500 to 10000 series

Specifications	ThermoFlex 3500	ThermoFlex 5000	ThermoFlex 7500	ThermoFlex 10000
Standard Temperature Range	5 °C to 40 °C (41 °F to 104 °F)			
Optional Temperature Range	5 °C to 90 °C (41 °F to 194 °F)			
Ambient Temperature Range	10 °C to 40 °C (50 °F to 104 °F)			
Temperature Stability	±0.1 °C			
Standard Cooling Capacity				
60 Hz at 20°C	3500 W / 11953 BTU	5000 W / 17076 BTU	7500 W / 25575 BTU	10000 W / 34100 BTU
50 Hz at 20°C	3050 W / 10416 BTU	4400 W / 15027 BTU	6425 W / 21910 BTU	8500 W / 28985 BTU
Reservoir Volume	7.2 Liters (1.9 gallons)		17.9 Liters (4.8 gallons)	
Refrigerant	R407C			
Physical Dimensions (HxWxD)	38.9 x 19.3 x 30.9 in (98.7 x 48.8 x 78.4 cm)		52.3 x 25.2 x 33.8 in (132.7 x 63.9 x 85.6 cm)	
Air-Cooled	38.9 x 19.3 x 30.9 in (98.7 x 48.8 x 78.4 cm)		45.9 x 25.2 x 33.8 in (116.6 x 63.9 x 85.6 cm)	
Water-Cooled	38.9 x 19.3 x 30.9 in (98.7 x 48.8 x 78.4 cm)		45.9 x 25.2 x 33.8 in (116.6 x 63.9 x 85.6 cm)	
P1 — Positive Displacement Pump	2.1 gpm @ 60 psig (7.9 lpm @ 4.1 bar)	—		
60 Hz	—	—		
50 Hz	1.7 gpm @ 60 psig (6.4 lpm @ 4.1 bar)	—		
P2 — Positive Displacement Pump	4.0 gpm @ 60 psig (15.1 lpm @ 4.1 bar)			
60 Hz	—			
50 Hz	3.3 gpm @ 60 psig (12.5 lpm @ 4.1 bar)			
T1 — Turbine Pump*	3.5 gpm @ 60 psid (13.2 lpm @ 4.1 bar)	—		
60 Hz	—	—		
50 Hz	2.5 gpm @ 60 psid (9.5 lpm @ 4.1 bar)	—		
T5 — Turbine Pump*	—	7.3 gpm @ 60 psid (27.6 lpm @ 4.1 bar)		
60 Hz	—	—		
50 Hz	—	6.2 gpm @ 60 psid (23.5 lpm @ 4.1 bar)		
P3 — Centrifugal Pump*	10 gpm @ 32 psid (37.9 lpm @ 2.2 bar)			
60 Hz	—			
50 Hz	10 gpm @ 20 psid (37.9 lpm @ 1.4 bar)			
P4 — Centrifugal Pump*	15 gpm @ 57 psid (56.8 lpm @ 3.9 bar)	—		
60 Hz	—	—		
50 Hz	15 gpm @ 34 psid (56.8 lpm @ 2.3 bar)	—		
P5 — Centrifugal Pump*	—	20 gpm @ 60 psid (75.7 lpm @ 4.1 bar)		
60 Hz	—	—		
50 Hz	—	20 gpm @ 35 psid (75.7 lpm @ 2.4 bar)		
Chiller Weight (with P2 pump)	264 lb (120 kg)		356 lb (161.5 kg)	
Voltage Options	208-230 V/60 Hz & 200 V/50 Hz ^{1,2}	Available	—	
230 V/50 Hz ¹	Available	—		
200-230 V/50-60 Hz Global Voltage ^{1,2}	Available	—		
208-230 V/60 Hz/3 phase & 200V/50 Hz ^{1,2}	—	Available		
400 V/50 Hz/3 phase	—	Available		
460 V/60 Hz/3 phase & 400 V/50 Hz/3 phase ^{1,2}	—	Available		
Compliance				
T5 Pump CSA compliance pending	¹ CE compliant ² CSA compliant			


Specifications obtained at sea level using water as the recirculating fluid, at a +20°C process setpoint, +25°C ambient condition, at nominal operating voltage. Cooling capacity based on chillers with P2 pumps with no backpressure. Other pumps will affect cooling capacity performance. Specifications subject to change.

*Pressure values for centrifugal and turbine pumps are differential pressures between the inlet and the outlet of the chiller.


105974_C_000

pumping capacity


P1 & P2 Pump




P3 & P4 Pump



P5 Pump




T5 Pump




cooling capacity

ThermoFlex 3500 & 5000



Cooling capacity based on chillers with P2 pumps with no backpressure. Other pumps will affect cooling capacity performance.

ThermoFlex 7500 & 10000





Note: Operation below +10°C requires the use of 50/50 EG/water or 50/50 PG/water

Cooling capacity based on chillers with P2 pumps with no backpressure. Other pumps will affect cooling capacity performance

15000 to 24000
watts of cooling



15000 to 24000 series


Specifications	ThermoFlex 15000	ThermoFlex 20000	ThermoFlex 24000
Standard Temperature Range	5 °C to 40 °C (41 °F to 104 °F)		
Ambient Temperature Range	10 °C to 40 °C (50 °F to 104 °F)		
Temperature Stability	±0.1 °C		
Standard Cooling Capacity 60 Hz at 20°C 50 Hz at 20°C	15000 W / 51228 BTU 12525 W / 42775 BTU	20000 W / 68304 BTU 16700 W / 57043 BTU	24000 W / 81964 BTU 21000 W / 71719 BTU
Reservoir Volume	17.9 liters (4.75 gallons)		
Refrigerant	R407C		
Physical Dimensions (H x W x D) Air-Cooled	49.0 x 46.5 x 30.9 in (124.4 x 118.1 x 78.6 cm)		58.6 x 46.5 x 30.9 in (148.9 x 118.1 x 78.6 cm)
Water-Cooled	49.0 x 46.5 x 30.9 in (124.4 x 118.1 x 78.6 cm)		
P3 — Centrifugal Pump* 60 Hz	10 gpm @ 32 psid (37.9 lpm @ 2.2 bar)		
50 Hz	10 gpm @ 20 psid (37.9 lpm @ 1.4 bar)		
P5 — Centrifugal Pump* 60 Hz	20 gpm @ 60 psid (75.7 lpm @ 4.1 bar)		
50 Hz	20 gpm @ 35 psid (75.7 lpm @ 2.4 bar)		
Chiller Weight (with P3 pump)	550 lb (249.5 kg)	650 lb (294.8 kg)	
Voltage Options 208-230 V/60 Hz/3 phase ^{1,2}	Available		
460 V/60 Hz/3 phase & 400 V/50 Hz/3 phase ^{1,2}	Available		
Compliance	  ¹ CE compliant ² CSA compliant <small>US 105974_C_000</small>		

Specifications obtained at sea level using water as the recirculating fluid at a +20°C process setpoint, +25°C ambient condition, at nominal operating voltage. Other fluids, process temperatures, ambient temperatures, altitude, or operating voltages will affect performance. *Pressure values for centrifugal pumps are the differential between the inlet and the outlet of the chiller. Specifications subject to change.


pumping capacity

cooling capacity

Pumping Capacity for Pump Options P3 & P5



ThermoFlex 15000/20000/24000



Coming Soon! T9 Pump

60 Hz - 15 gpm @ 85 psid (56 lpm @ 5.9 bar)
 50 Hz - 15 gpm @ 75 psid (56 lpm @ 5.2 bar)
Increased flow and pressure for your demanding applications!


Cooling capacity based on chiller with P3 pumps with no backpressure. Other pumps will affect cooling capacity performance.

Note: Operation below +10°C requires the use of 50/50 EG/water or 50/50 PG/water

Full flow filter ensures clean fluid to protect your application and maximize recirculation system life.

Easily removable condenser grill and air filter allow for quick and simple cleaning to optimize chiller performance and maximize component life.

Integrated funnel fill for easy filling.



Part Number	Accessories
Seismic Tiedowns	
097374	Seismic Tiedown Kit for ThermoFlex 900-2500
095139	Seismic Tiedown Kit for ThermoFlex 3500 - 5000
096502	Seismic Tiedown Kit for ThermoFlex 7500 - 10000
Plumbing Packages	
59900000012	50' of 1"ID Polybraided hose comes with 1" hose barbs, insulation and clamps. For use with the ThermoFlex 7500 - 24000 with the P3, P5 and T5 pumps
59900000011	25' of 1"ID Polybraided hose comes with 1" hose barbs, insulation and clamps. For use with the ThermoFlex 7500 - 24000 with the P3, P5 and T5 pumps
61100000107	10m Standard Temp Plumbing Package for all ThermoFlex 3500 - 5000 with P3, P4 pumps (3/4" NPT)
61100000105	50' High Temp Plumbing Package for all ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
61100000104	25' High Temp Plumbing Package for all ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
61100000100	50' Standard Temp Plumbing Package for all ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
61100000004	25' Standard Temp Plumbing Package for all ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
Filter Bags	
59800000002	2 ea. 35 micron replacement filter bags for ThermoFlex 900 - 5000
59800000003	2 ea. 100 micron replacement filter bags for ThermoFlex 900 - 5000
59800000004	2 ea. 100 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 900 - 1400
59800000005	2 ea. 35 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 900 - 1400
59800000006	2 ea. 100 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 2500
59800000007	2 ea. 35 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 2500
59800000008	2 ea. 100 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 3500 - 5000
59800000009	2 ea. 35 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 3500 - 5000
59800000013	2 ea. 35 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 7500 - 10000
59800000014	2 ea. 100 micron replacement filter bags and 1 ea. Front grill/filter for ThermoFlex 7500 - 10000
61100000101	2 ea. 35 micron replacement filter bags for ThermoFlex 7500 - 24000
61100000102	2 ea. 100 micron replacement filter bags for ThermoFlex 7500 - 24000
59800000015	2 ea. 250 micron replacement filter bags for ThermoFlex 7500 - 24000
Fittings	
59800000011	2 ea. 1/2" MPT to 3/8" ID brass hose barbs. For use with ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
External Pressure Reducers	
34200000025	External Pressure Reducer for use with ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
34200000026	External Pressure Reducer for use with ThermoFlex 3500 - 5000 with P3 or P4 pumps. (3/4" NPT)
34200000027	External Pressure Reducer for use with ThermoFlex 7500 - 24000 with P3, P5, T5 and T9 pumps (1" NPT)
External Flow Control Kits	
61100000106	External Flow Control Kit for use with ThermoFlex 900 - 10000 with P1, P2 or T1 pumps (1/2" NPT)
34200000028	External Flow Control Kit for use with ThermoFlex 3500 - 5000 with P3 or P4 pumps. (3/4" NPT)
34200000029	External Flow Control Kit for use with ThermoFlex 7500 - 24000 with P3, P5, T5 and T9 pumps (1" NPT)
Communication Cable	
42600000044	25' RS232/RS485 Communication Cable Assembly. Fits all chillers with RS232/RS485 with digital communication option
Software	
42200000004	NEScom control/monitoring PC software

© 2013 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Results may vary under different operating conditions. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

www.thermoscientific.com/thermoflex

North America: USA/Canada tollfree: +1 (800) 258-0830; USA: +1 (603) 436-9444 or info.tc.us@thermofisher.com
Europe: Benelux: +31 (0) 76 579 55 55 or info.tc.nl@thermofisher.com; France: +33 (0) 1 60 92 48 00 or info.tc.fr@thermofisher.com;
 Germany: +49 (0) 721 4 09 44 44 or info.tc.de@thermofisher.com; United Kingdom: +44 (0) 8706 099 254
Asia: China: +81 3 5826 1616 or info.tc.china@thermofisher.com; India: +91 (22) 27 78 11 01 or contact.lpg.in@thermofisher.com;
 Japan: +81-3-5826-1616 or info.lpg.jp@thermofisher.com