

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Revision Date 09-Feb-2024 Revision Number 8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

Cat No. : 243260000; 243262500

Molecular Formula Na

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals. Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 2 (H225) Substances/mixtures which, in contact with water, emit flammable gases Category 1 (H260)

Health hazards

Aspiration Toxicity Category 1 (H304)
Skin Corrosion/Irritation Category 1 B (H314)

ACR24326

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

Revision Date 09-Feb-2024

Serious Eye Damage/Eye Irritation

Reproductive Toxicity

Specific target organ toxicity - (single exposure)

Specific target organ toxicity - (repeated exposure)

Category 1 (H318) Category 2 (H361d)

Category 3 (H336)

Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure if inhaled

EUH014 - Reacts violently with water

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P402 + P404 - Store in a dry place. Store in a closed container

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Toluene	108-88-3	203-625-9	70	Flam. Liq. 2 (H225)
				Asp. Tox. 1 (H304)
				Skin Irrit. 2 (H315)
				STOT SE 3 (H336)

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

				Repr. 2 (H361d) STOT RE 2 (H373)
Sodium	7440-23-5	EEC No. 231-132-9	30	Water-react. 1 (H260) Skin Corr. 1B (H314) Eye Dam. 1 (H318)
				EUH014

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact Immediate medical attention is required. Rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes.

Skin Contact Immediate medical attention is required. Wash off immediately with plenty of water for at

least 15 minutes.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting

occurs naturally, have victim lean forward.

Inhalation Immediate medical attention is required. Remove to fresh air. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If not breathing, give artificial respiration. Risk of serious damage to the lungs (by aspiration).

Revision Date 09-Feb-2024

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated:

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Dry chemical. approved class D extinguishers. clay. sodium carbonate. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

Revision Date 09-Feb-2024

Hazardous Combustion Products

Hydrogen.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing. Remove all sources of ignition. Take precautionary measures against static discharges. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharges. Handle product only in closed system or provide appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Protect from moisture. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Keep from any possible contact with water. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 4.3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Toluene	STEL: 100 ppm 15 min	TWA: 50 ppm (8hr)	TWA: 192 mg/m ³ 8 hr.
	STEL: 384 mg/m ³ 15 min	TWA: 192 mg/m³ (8hr)	TWA: 50 ppm 8 hr.
	TWA: 50 ppm 8 hr	STEL: 100 ppm (15min)	STEL: 384 mg/m ³ 15 min
	TWA: 191 mg/m ³ 8 hr	STEL: 384 mg/m ³ (15min)	STEL: 100 ppm 15 min
	Skin	Skin	Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

	Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)		
I	Toluene				DNEL = 384mg/kg		
	108-88-3 (70)				bw/day		

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)	
Toluene 108-88-3 (70)	DNEL = 384mg/m ³	DNEL = 384mg/m ³	DNEL = 192mg/m ³	DNEL = 192mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

	Component	Fresh water			Microorganisms in	` ' '
L			sediment		sewage treatment	
	Toluene	PNEC = 0.68mg/L	PNEC =	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg
	108-88-3 (70)		16.39mg/kg			soil dw
			sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Toluene	PNEC = 0.68mg/L	PNEC =			
108-88-3 (70)		16.39mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment Eye Protection

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

Revision Date 09-Feb-2024

EU standard Glove material Breakthrough time Glove thickness Glove comments See manufacturers EN 374 Viton (R) (minimum requirement)

recommendations Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Hand Protection

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Protective gloves

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Slurry Liquid

Appearance No information available

Odor Rotten-egg like **Odor Threshold** No data available 97.80 °C / 208 °F **Melting Point/Range Softening Point** No data available **Boiling Point/Range** No information available

Highly flammable On basis of test data Flammability (liquid) Flammability (solid,gas) Reacts violently with water, liberating Based on available literature

extremely flammable gases

Explosion Limits Lower 1.2 Upper 7

Flash Point 4 °C / 39.2 °F Method - No information available

Autoignition Temperature 115 °C / 239 °F **Decomposition Temperature** No data available рΗ No information available **Viscosity** No data available

Water Solubility Reacts violently with water Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component Toluene 2.73

No data available **Vapor Pressure**

Density / Specific Gravity 0.900

Bulk Density Not applicable Liquid

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

The state of the s

Revision Date 09-Feb-2024

Vapor Density No data available (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular FormulaNaMolecular Weight22.98

Explosive Properties Vapors may form explosive mixtures with air

Substances/mixtures which, in contact with water, emit flammableEmitted gas ignites spontaneously

Gas(es) = Hydrogen

gases

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes

10.2. Chemical stability

Reacts violently with water, liberating extremely flammable gases.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.

Hazardous Reactions Reacts violently with water, liberating extremely flammable gases.

10.4. Conditions to avoid

Incompatible products. Exposure to moist air or water. Keep away from open flames, hot

surfaces and sources of ignition.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

Hydrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information No acute toxicity information is available for this product

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h	

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

No data available Respiratory

No data available Skin

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

Teratogenicity Teratogenic effects have occurred in experimental animals.

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Respiratory system, Eyes, Ears, Neuropsychological effects. **Target Organs**

Category 1 (j) aspiration hazard;

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and

Revision Date 09-Feb-2024

danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects The product contains following substances which are hazardous for the environment.

Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h static
	5-7 mg/L LC50 96 h	(Daphnia magna)	(Pseudokirchneriella subcapitata)
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L, 48h	EC50: > 433 mg/L, 96h
	28 mg/L LC50 96 h	Static (Daphnia magna)	(Pseudokirchneriella subcapitata)
	12 mg/L LC50 96 h		

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

12.2. Persistence and degradability

Soluble in water, Persistence is unlikely, based on information available. **Persistence**

Component	Degradability
Toluene	86% (20d)
108-88-3 (70)	

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

Revision Date 09-Feb-2024

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component log Pow **Bioconcentration factor (BCF)** Toluene 2.73 90

12.4. Mobility in soil The product is water soluble, and may spread in water systems. Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

This product does not contain any known or suspected endocrine disruptors **Endocrine Disruptor Information**

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

> application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH

and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN3482 14.1. UN number

14.2. UN proper shipping name ALKALI METAL DISPERSION, FLAMMABLE

14.3. Transport hazard class(es) 4.3 3 **Subsidiary Hazard Class** 14.4. Packing group Ι

ADR

14.1. UN number UN3482

ALKALI METAL DISPERSION, FLAMMABLE 14.2. UN proper shipping name

4.3 14.3. Transport hazard class(es) **Subsidiary Hazard Class** 3 14.4. Packing group Ι

Revision Date 09-Feb-2024

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

<u>IATA</u>

14.1. UN number UN3482

14.2. UN proper shipping name ALKALI METAL DISPERSION, FLAMMABLE

14.3. Transport hazard class(es)4.3Subsidiary Hazard Class314.4. Packing groupI

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Toluene	108-88-3	203-625-9	ı	ı	X	X	KE-33936	Χ	X
Sodium	7440-23-5	231-132-9	-	-	X	X	KE-31338	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Toluene	108-88-3	X	ACTIVE	Х	-	X	Х	Х
Sodium	7440-23-5	Х	ACTIVE	Х	-	Χ	Χ	Х

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Sodium	7440-23-5	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -		
_		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report		

Revision Date 09-Feb-2024

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

		Notification	Requirements
Toluene	108-88-3	Not applicable	Not applicable
Sodium	7440-23-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Toluene	WGK3	
Sodium	WGK1	

Component	France - INRS (Tables of occupational diseases)
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis,RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene	Prohibited and Restricted	Group I	
108-88-3 (70)	Substances		Į.

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H260 - In contact with water releases flammable gases which may ignite spontaneously

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

EUH014 - Reacts violently with water

Legend

Sodium, 30 wt% dispersion in toluene, <0.1 mm particle size

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

Revision Date 09-Feb-2024

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances AICS - Australian Inventory of Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer

DNEL - Derived No Effect Level Predicted No Effect Concentration (PNEC)

RPE - Respiratory Protective Equipment LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration POW - Partition coefficient Octanol:Water PBT - Persistent, Bioaccumulative, Toxic vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of ICAO/IATA - International Civil Aviation Organization/International Air Dangerous Goods by Road Transport Association

IMO/IMDG - International Maritime Organization/International Maritime MARPOL - International Convention for the Prevention of Pollution from

Dangerous Goods Code Ships

OECD - Organisation for Economic Co-operation and Development ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound) **BCF** - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date 09-Feb-2024 **Revision Summary** Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet