

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 04-Jun-2009 Revision Date 06-Oct-2023 Revision Number 8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: <u>Sodium methoxide, 0.5M solution in methanol</u>

Cat No. : 445880000; 445881000; 445888000

Synonyms Sodium methylate

Molecular Formula C H3 Na O

Unique Formula Identifier (UFI) KW70-73NS-TX0C-SQX7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG,

United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel,

Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

information services 01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 1 (H370)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H225 Highly flammable liquid and vapor
- H319 Causes serious eye irritation
- H315 Causes skin irritation
- H370 Causes damage to organs
- H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P311 - Call a POISON CENTER or doctor/physician

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Not applicable

Water reactive

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	97-98	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Sodium methoxide	124-41-4	EEC No. 204-699-5	2-3	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Self-heat. 1 (H251) Flam. Sol. 1 (H228) Met. Corr. 1 (H290) EUH014

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be

headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed

Sodium methoxide, 0.5M solution in methanol

Revision Date 06-Oct-2023

then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany) Class 3

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m³ TWA	TWA: 260 mg/m ³ 8 hr	TWA: 260 mg/m ³ 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m ³ STEL		STEL: 780 mg/m ³ 15 min
			Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

	Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ī	Methyl alcohol		DNEL = 20mg/kg		DNEL = 20mg/kg
	67-56-1 (97-98)		bw/day		bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl alcohol 67-56-1 (97-98)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent Microorganisms in Soil (Agricultur	;)
		sediment	sewage treatment	

Sodium methoxide, 0.5M solution in methanol

Revision Date 06-Oct-2023

Γ	Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg
L	67-56-1 (97-98)		sediment dw			soil dw
Γ	Sodium methoxide	PNEC = 154mg/L	PNEC =	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 23.5mg/kg
1	124-41-4 (2-3)		570.4mg/kg		_	soil dw
L			sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol 67-56-1 (97-98)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Sodium methoxide 124-41-4 (2-3)	PNEC = 15.4mg/L				

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

Odor
Odor No information available
No data available
No data available
No data available
-98 °C / -144.4 °F
No data available
No data available

Boiling Point/Range65 °C / 149 °F@ 760 mmHgFlammability (liquid)Highly flammableOn basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 5.5 vol% Upper 44 vol%

Flash Point 11 °C / 51.8 °F Method - No information available

Autoignition Temperature
Decomposition Temperature
pH
Viscosity
Water Solubility
Solubility in other solvents

455 °C / 851 °F
No data available
No information available
Reacts with water
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74Sodium methoxide-0.75

Vapor Pressure No data available

Density / Specific Gravity 0.800

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C H3 Na O Molecular Weight 54.02

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Sodium methoxide	1687 mg/kg (Rat)	>2000 mg/kg (Rat)	-

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

RespiratorySkin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 (97-98)	Guinea Pig Maximisation Test		
	(GPMT)		

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Mutagenic effects have occurred in humans

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation	NOAEC =
67-56-1 (97-98)		2 Generation	1.3 mg/l (air)
		1 41 4 14 66 4 1 1	

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental EffectsDevelopmental effects have occurred in experimental animals. Component substance is

listed on California Proposition 65 as a developmental hazard. Teratogenic effects have occurred in experimental animals.

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve, Central nervous system (CNS).

Teratogenicity

Sodium methoxide, 0.5M solution in methanol

Revision Date 06-Oct-2023

(i) STOT-repeated exposure: Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects See actual entry in RTECS for complete information The toxicological properties have not

been fully investigated.

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting. Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

11.2. Information on other hazards

Assess endocrine disrupting properties for human health. This product does not contain any **Endocrine Disrupting Properties**

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

This product contains the following substance(s) which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl alcohol	Pimephales promelas: LC50 >	EC50 > 10000 mg/L 24h	
	10000 mg/L 96h		

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	

12.2. Persistence and degradability No information available

Persistence Persistence is unlikely, based on information available.

Degradability Reacts with water.

Component		Degradability
Methyl alcohol		DT50 ~ 17.2d
67-56-1 (97-98)		>94% after 20d

Degradation in sewage

treatment plant

Water reactive.

Bioaccumulation is unlikely 12.3. Bioaccumulative potential

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Sodium methoxide	-0.75	No data available

The product contains volatile organic compounds (VOC) which will evaporate easily from all 12.4. Mobility in soil

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

assessment

Not applicable. Water reactive. Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Sodium methoxide, 0.5M solution in methanol

Revision Date 06-Oct-2023

Page 10/13

Endocrine Disruptor Information This product doe

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1992

14.2. UN proper shipping name Flammable liquid, toxic, n.o.s.

Technical Shipping Name (Contains methanol and sodium methoxide)

14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

ADR

14.1. UN number UN1992

14.2. UN proper shipping name Flammable liquid, toxic, n.o.s.

Technical Shipping Name (Contains methanol and sodium methoxide)

14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

<u>IATA</u>

14.1. UN number UN1992

14.2. UN proper shipping name Flammable liquid, toxic, n.o.s.

Technical Shipping Name (Contains methanol and sodium methoxide)

14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

Sodium methoxide, 0.5M solution in methanol

Revision Date 06-Oct-2023

14.5. Environmental hazardsNo hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	Х	Х	KE-23193	Х	Х
Sodium methoxide	124-41-4	204-699-5	-	-	Х	X	KE-23196	X	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	X	ACTIVE	X	-	X	X	X
Sodium methoxide	124-41-4	Х	ACTIVE	X	-	X	X	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Sodium methoxide	124-41-4	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

	Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
	Methyl alcohol	67-56-1	500 tonne	5000 tonne
Ī	Sodium methoxide	124-41-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl alcohol	WGK 2	Class I: 20 mg/m³ (Massenkonzentration)
Sodium methoxide	WGK2	

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol 67-56-1 (97-98)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H228 - Flammable solid

H251 - Self-heating; may catch fire

H290 - May be corrosive to metals

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H370 - Causes damage to organs

EUH014 - Reacts violently with water

H302 - Harmful if swallowed

Legend

Sodium methoxide, 0.5M solution in methanol

Revision Date 06-Oct-2023

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent. Bioaccumulative. Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

NZIoC - New Zealand Inventory of Chemicals

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships ATE - Acute Toxicity Estimate

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date 04-Jun-2009 **Revision Date** 06-Oct-2023 **Revision Summary** Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet